

Black Body Sources

Nagman Dual Black Body Calibration System

*Space Saver Calibrator for
Simultaneous Measurement of
Low & Medium Temperatures*

Basic Accuracy : $\pm 0.5\%$ F.S.

For Non-contact Pyrometer Calibration

Model

BBSD

- Enables simultaneous measurement of 2 Pyrometers / Quick Measurement in 2 Points over the range
- Compact, Light Weight, Bench-top & Portable
- Dual Ranges : 50 to 300°C & 250 to 600°C
- Excellent Accuracy & Stability
- High Emissivity, wide Aperture
- Auto-tune PID Controller
- Low Power Consumption
- Cost effective – Best Value for Money
- RS-232 Computer Interface – Optional
- Calibration Management Software – Optional



SPECIFICATIONS

Models	Chamber 1	Chamber 2
Range	50 to 300°C	250 to 600°C
Accuracy	Within 0.5% of indicated temperature (Min. 1°C)	Within 0.5% of indicated temperature (Min. 2°C)
Stability	±0.5°C	
Resolution	0.1°C	
Temperature Control	Auto-tune PID Controller	
Heating time (to max.)	45 Minutes	
Stabilization time	30 minutes	
Temperature Readout	°C / °F selectable	
Emissivity	0.98	
Aperture size	φ 25 mm	
Power Supply	230 VAC / 50 Hz	
Dimension	450 x 410 x 190 mm (W x D x H)	
Weight	14 Kgs	
Housing / Mounting	Bench-top / Table-top (Portable)	

STANDARD DELIVERY

- Basic Instrument
- Mains Cable
- Spare Fuses
- Traceable Calibration Certificate
- Instruction Manual

OPTIONAL

- RS-232 Computer Interface
- "Caltemp" Calibration Software
- Contact Thermocouple (to measure cavity temperature)
- Calibration Certificate from NABL Accredited – as per ISO/IEC 17025:2005 Laboratory

Product of

Nagman Instruments & Electronics (P) Ltd.

- Comprehensive Calibration Solutions (Standards / Systems / Packages / Software / Services)
Chennai – 600 123. INDIA.



Domestic Sales 044-2252 2800, 2252 3240 Fax 044 – 2252 3240 E-Mail mktgchennai@nagman.com
International Sales +91-44-26811704, 26811708 Fax +91-44-26811703 E-Mail exports@nagman.com

www.nagman.com

